

## PARKING SYSTEMS

# PKX

## Automatic Payment Station

Designed to improve car park profitability, the **PKX Automatic Payment Station** that is part of our 'open platform', has been designed with **low maintenance and high availability components** that turns it into a complete multifunction station suitable for **reliable operation in self-attended mode**.

It is capable of handling **any type of payment** while acting as an **information point, assistance, advertising, product and customized services sales**, thanks to features such as the 23.8-inch portrait format screen.

It maintains its compatibility with the **most advanced version of our PMS LINCE 7**, thus allowing the configuration for all payment types, from the most traditional based on a physical ticket, to the ticketless scenarios based on license plate payment from the APS (virtual ticket).



### VIDEO ASSISTANCE

Easy communication with the user



### QR TECHNOLOGY

Integration with 3<sup>rd</sup> Party and APPs



### MULTIFUNCTION STATION

Ready for different uses



### STANDARD COLOURS

5368A0837

RAL 9005

Available in a wide range of colors that can be fully customized for each customer according to the RAL color chart.

# CAME PARKARE

[CAME.COM/PARKARE](http://CAME.COM/PARKARE)

23.8"

### 23.8" TOUCHSCREEN

Portrait format

### THERMAL PRINTER

Maximum availability for the release of products and/or receipts

### REMOTELY ATTENDED

Low cost supervision

### LOW MAINTENANCE

Ongoing operation

## TECHNICAL DATA

Operating Temperature (°C)	0 ÷ 50 <b>(1)</b>
Operating Temperature with heater (°C)	-20 ÷ 50
Power Supply (VAC)	100 ÷ 120 / 200 ÷ 240
Input Frequency (Hz)	50 / 60
Max. Power Consumption (W)	360 (typical power: 100)
Max. Power Consumption with heater (Indoor) (W)	610
Max. Power Consumption with heater (Outdoor) (W)	910
Dimensions (H x W x D) (mm)	1485 x 740 x 500 <b>(2)</b>
Storage Temperature (°C)	0 ÷ 40
Average Product Life in Storage (years)	7

**(1)** The Operating Temperature with UPS is 40°C. The UPS is an optional component.

**(2)** Minimum height. Please consult the different available heights (1485 – 1685 mm)

## FEATURES

Some of the components/devices may be optional.

### USER INTERFACE

- 23.8" touchscreen in portrait format.
- Operation in 4 languages (defined by the customer).
- IP intercom based on SIP protocol for communication with the central office.
- Sleep mode for low power consumption.
- Low-latency facial camera integrable with the intercom.
- High-brightness outdoor screen (optional).

### COMPONENTS

- Embedded PC based on x86 architecture with SSD storage.
- Internal ventilation system.
- Heating system.
- RFID proximity card reader for subscriber control and integrated QR reader with the capacity to read codes on ticket support, printed paper and mobile devices (smartphones, tablets...).
- Thermal receipt printer and/or ticket issuer.
- Uninterruptible power supply system (UPS), which allows the cashier to complete ongoing operations in the event of a power failure.

### EXTERNAL FINISH AND SECURITY

- 2 mm AP02 steel sheet cabinet, with anti-corrosion coating and powder-coated with polyester resins, free of TGIC.
- Front door with security lock and multiple locking points.
- Micro sensors for detection: door opening, lock, coin box removal, hoppers removal and note box removal.

### PAYMENT MODULES

- EMV reader for credit card with chip and proximity payments (NFC). Keyboard module the introduction of PIN code, optional.
- Ask availability for approval in different countries.
- Banknote reader, with capacity to read 64 different banknotes on 4 sides and escrow function. It has a 300 banknote stacker (optional).
- Banknote acceptor with recycler system (optional). It has multiescrow and recycling capacity for 2 denominations, with up to 30 banknotes in each recycler hopper. Single slot.
- Coins module with change giving, accepting up to 16 denominations of different coins and automatic return of 4 different values.
- 3 self-charging coin hoppers, with capacity of 750 coins/each.
- 1 manual reload hopper (optional) configurable for 750 coins or 1.500 coins capacity.

