


Product image	DESCRIPTION	Item Nr. Bizcanli	TYPE / CODE	Output torque Nm	Paperboard Box dimensions in mm	Specification	UNIT WEIGHT (Kg)
 	ALY63-251 GEARMOTOR WITH LIMIT SWITCH	Y63251	0,25 Kw 1rpm 380V. 50Hz	300 Nm	330X510X270	Aluminium die cast housing with self locking 3 stage gear set Mounting plate options Chain coupling with / without shaft options	20,25
	ALY63-253 GEARMOTOR WITH LIMIT SWITCH	Y63253	0,25 Kw 3 rpm 380V. 50Hz	280 Nm	330X510X271		20,25
	ALY63-373 GEARMOTOR WITH LIMIT SWITCH	Y63373	0,37 Kw3 rpm 380V. 50Hz	380 Nm	330X510X272		21,20
	ALY63-375 GEARMOTOR WITH LIMIT SWITCH	Y63375	0,37Kw 5 rpm 380V. 50Hz	240 Nm	330X510X273		21,20
	ALY63-553 GEARMOTOR WITH LIMIT SWITCH	Y63553	0,55Kw 5 rpm 380V. 50Hz	550 Nm	330X510X274		22,50
	ALY75-373 GEARMOTOR WITH LIMIT SWITCH	Y75373	0,37 Kw 3 rpm 380V. 50Hz	450 Nm	330X540X295		23,90
	ALY75-553 GEARMOTOR WITH LIMIT SWITCH	Y75553	0,55 Kw 3 rpm 380V. 50Hz	650 Nm	330X540X295		25,60
	ALY75-555 GEARMOTOR WITH LIMIT SWITCH	Y75555	0,55 Kw 5 rpm 380V. 50Hz	400 Nm	330X540X295		25,60
	ALY75-753 GEARMOTOR WITH LIMIT SWITCH	Y75753	0,75 Kw 3 rpm 380V. 50Hz	800 Nm	330X540X295		27,00
	ALY90-553 GEARMOTOR WITH LIMIT SWITCH	Y90553	0,55 Kw 3 rpm 380V. 50Hz	800 Nm	350X590X325		29,60
	ALY90-753 GEARMOTOR WITH LIMIT SWITCH	Y90753	0,75 Kw 3 rpm 380V. 50Hz	1000 Nm	350X590X325		30,70
	ALY90-755 GEARMOTOR WITH LIMIT SWITCH	Y90755	0,75 Kw 5 rpm 380V. 50Hz	680 Nm	350X590X325		30,70
  	ALS35	S3517	Manual Gearbox	32 Nm	210X560X265	Aluminium die cast housing with self locking worm gear set Ratio i:7 / Single or Double output shaft With/Without roller mechanism	1,76
	ALS35 with PIPE GUIDE	S3517-PG	Manual Gearbox	32 Nm	330X540X295		3,00
	ALS35 with MOUNTING PLATE	S3517-MP	Manual Gearbox	32 Nm	330X540X295		3,00
	ALS63	S63130	Manual Gearbox with pulley	350 Nm	246X265X220	Aluminium die cast housing with self locking worm gear set With/Without chain coplings	15,50
	ALS85	S85130	Manual Gearbox with pulley	450 Nm	256X256X300		22,00
 	RACK & PINION SETS 120	RPS-120	STRAIGHT 120 CM	12 Nm / 450 N	100X120X80	Powder metal pinion with bronze bearings Pinion housing : 1,5 mm galvanised steel Rack : 2,5 mm galvanised steel Rack Length : On request	2,00
	RACK & PINION SETS 130	RPS-130	STRAIGHT 130 CM	12 Nm / 450 N	100X130X80		2,15
	RACK & PINION SETS 140	RPS-140	STRAIGHT 140 CM	12 Nm / 450 N	100X140X80		2,30
	RACK & PINION SETS 150	RPS-150	STRAIGHT 150 CM	12 Nm / 450 N	100X150X80		2,45
	RACK & PINION SETS 160	RPS-160	STRAIGHT 160 CM	12 Nm / 450 N	100X160X80		2,60
	RACK & PINION SETS 180	RPS-180	STRAIGHT 180 CM	12 Nm / 450 N	100X180X80		2,75
	RACK & PINION SETS 100	RPS-100-C	CURVED 100 CM	12 Nm / 450 N	100X100X80		1,85
	RACK & PINION SETS 120	RPS-120-C	CURVED 120 CM	12 Nm / 450 N	100X120X80		2,00
	RACK & PINION SETS 130	RPS-130-C	CURVED 130 CM	12 Nm / 450 N	100X130X80		2,15
	RACK & PINION SETS 140	RPS-140-C	CURVED 140 CM	12 Nm / 450 N	100X140X80		2,30
	RACK & PINION SETS 150	RPS-150-C	CURVED 150 CM	12 Nm / 450 N	100X150X80		2,45
	RACK & PINION SETS 160	RPS-160-C	CURVED 160 CM	12 Nm / 450 N	100X160X80		2,60
	RACK & PINION SETS - Economical type 120	RPS-120-E	STRAIGHT 120 CM	9 Nm	246X265X220	Pinion housing : 1,5 mm galvanised steel Rack : 2,5 mm galvanised steel Rack Length : On request	1,90
	RACK & PINION SETS - Economical type 130	RPS-130-E	STRAIGHT 130 CM	9 Nm	246X265X220		2,00
	RACK & PINION SETS - Economical type 150	RPS-150-E	STRAIGHT 150 CM	9 Nm	246X265X220		2,25

Product image	DESCRIPTION	Item Nr. Bizcanli	TYPE / CODE	Output torque Nm	Paperboard Box dimensions in mm	Specification	UNIT WEIGHT (Kg)
	SCREENING PINION SET with couplings	SPS17	WITH RACK SHAFT CONNECTION	7Nm / 27 Nm	246X265X220	Galvanised steel Housing Ratio i: 1,82 Ratio i:7 / Single or Double output shaft Rack drive: 7,5cm / per round	2,40
	SCREENING RACK 3 Mt	SR-3000	ZINC COATED	7Nm / 27 Nm	80X3000X80		4,50
	SCREENING RACK 5 Mt	SR-5000	ZINC COATED	7Nm / 27 Nm	80X5000X80		7,50
	HANGING BEARINGS - BEARING SUPPORTS	HB-345	DIA: 34,5 mm.	-	246X260X300	Galvanised steel Housing Plastic roller ring	0,25
	RACK HOLDER ALUMINIUM T PART	RHAT	with Bolt and Nut	-	210X560X265	Material : Aluminium Extrusion	0,08
	ALK SIDE ROLL GEARMOTORS ALK40-2512	K402512	0,25 Kw 12rpm 380V. 50Hz	71 Nm	330X510X270	Aluminium die cast housing with self locking worm gear set Roller mechanism options With limit switch controll	10,20
	ALK SIDE ROLL GEARMOTORS ALK40-2515	K402515	0,25 Kw 12rpm 380V. 50Hz	65 Nm	330X510X270		10,20
	ALK SIDE ROLL GEARMOTORS ALK50-2512	K502512	0,25 Kw 12rpm 380V. 50Hz	90 Nm	330X510X270		11,85
	ALK SIDE ROLL GEARMOTORS ALK50-2515	K502515	0,25 Kw 18rpm 380V. 50Hz	80 Nm	330X510X270		11,85
	ALK SIDE ROLL GEARMOTORS ALK50-3709	K503709	0,37 Kw 9rpm 380V. 50Hz	108 Nm	330X510X270		12,85
	ALK SIDE ROLL GEARMOTORS ALK50-3712	K503712	0,37 Kw 12rpm 380V. 50Hz	94 Nm	330X510X270		12,75
	ALK SIDE ROLL GEARMOTORS ALK50-3715	K503715	0,37 Kw 14rpm 380V. 50Hz	90 Nm	330X510X270		12,75
	ALK SIDE ROLL GEARMOTORS ALK63-5512	K635512	0,55 Kw 12rpm 380V. 50Hz	199 Nm	330X510X270		16,85
ALK SIDE ROLL GEARMOTORS ALK63-5515	K635515	0,55 Kw 14rpm 380V. 50Hz	180 Nm	330X510X270	16,85		
	TRUSS-RAIL VENTILATION RACK DRIVES 52 S750	BZC52-750	BZC52 S750	32,5 Nm	80X120X140	zinc-coated housing with foot mounting Output rack force 5200 N Single stage reduction	8,12
	TRUSS-RAIL VENTILATION RACK DRIVES 52 S900	BZC52-900	BZC52 S900	32,5 Nm	80X120X140		8,80
	TRUSS-RAIL VENTILATION RACK DRIVES 52 S1100	BZC52-1100	BZC52 S1100	32,5 Nm	80X120X140		9,70
	TRUSS-RAIL VENTILATION RACK DRIVES 100 S750	BZC100-750	BZC100 S750	70 Nm	80X120X140	not in product range	8,12
	TRUSS-RAIL VENTILATION RACK DRIVES 100 S900	BZC100-900	BZC100 S900	70 Nm	80X120X140		8,80
	TRUSS-RAIL VENTILATION RACK DRIVES 100 S1100	BZC100-1100	BZC100 S1100	70 Nm	80X120X140		9,70
	BZC TRUSS RAIL RACK DRIVE CAST IRON 75	BZC-PP75	BZC-PP-75 -15000N-	65 Nm	80X120X160	Cast iron housing with heat treated gear sets Pipe connection couplings are included	11,55
	BZC TRUSS RAIL RACK DRIVE CAST IRON 100	BZC-PP100	BZC-PP-100 -15000N-	65 Nm	80X120X160		15,40
	BZC TRUSS RAIL RACK DRIVE CAST IRON 125	BZC-PP125	BZC-PP-125 -15000N-	65 Nm	80X120X160		19,25
	Circulation Fan -0,25 Kw 380V	CF-25380	7400m3/ h - 1400 rpm DIA: 46cm	-	50X50X50	Galvanised Steel painted housing Galvanised Steel blades	14,50
	Circulation Fan -0,37 KW 380V	CF-37380	7400m3/ h - 1400 rpm DIA: 46cm	-	50X50X50		14,50
	Exhaust Fan 100 x 100	EF100	18.000m3/h - 0,55 Kw 1400 380V. 50 Hz	-	100X100X50	Galvanised Steel housing Galvanised Steel blades	50
	Exhaust Fan 140 x 140	EF140	42.000m3/h - 1,1 Kw 1400 380V. 50 Hz	-	140X140X50		79