inoMini

inopor® Cross-flow Filtration Plant

The ideal test unit for investigating ceramic membrane elements using the cross-flow method: Due to its compact and robust design, the inoMini is the optimal filtration unit for laboratory trials and your initial membrane suitability tests.



inopor® -
a Rauschert brand
Industriestraße 1
98669 Veilsdorf

Managing director
Dr. Richard Metzler

+49 3685-685 257
contact@inopor.com
www.inopor.com

inoMini

Technical Data:

- Max. operating pressure: 40 bar
- Max. working temperature: 60 °C
- Max. volume flow rate: 10 l/min
- Energy consumption: 3 phases, 400 V, 50/60 Hz, 1.5 kW
- Operating mode: manual
- Data processing: manual
- Dimensions (width x depth x height): 940 x 660 x 850 mm
- Weight: approx. 130 kg

Suitable filter elements:

- Single channel geometry: 500 mm length, OD/ID = 10/7 mm

Components:

- Pump: plunger pump
- Double-walled container: 4.5 liter capacity
- Flowmeter: variable area flowmeter
- Heat exchanger
- Pressure relief valve

Wetted Parts:

- Stainless steel, FPM, NBR, EPDM, PTFE, TPX, glass, PVC

Accessories:

- Connections for cooling water: included
- Module housing: included
- Table frame: optional
- Testing cell for polymeric flat sheet membranes: optional

Please contact us for further support.

Information in this document about products, systems and/or services may change without notice due to technical development. There is no guarantee of success based on the information provided. It is the user's responsibility to validate products in their unique application. Please consult your inopor contact or visit www.inopor.com for more information.
Status: July 2020.