

IMPORTANT! Please read all instructions before installing.

Thank you for purchasing a Shakespeare product. Shakespeare works hard to build reliability and durability into all of its products. Before installing, please study the diagram and check parts supplied against those listed

The 7187-SL is a new concept of Starlink Mount. Designed for the commercial marine market and for the harshest situations.

Note—Suitable for FLAT HIGH PERFORMANCE ANTENNA

Tools required:

- Drill for bulkhead / Deck
- Screwdriver for installation

Installation Instructions (note for FLAT HIGH PERFORMANCE ANTENNA ONLY)

Choose a mounting location as high as feasible, as free as possible from obstructions, and as far as possible from other antennas or strong sources of Radio frequency.

1. The mount can be installed on a Horizontal or Vertical surface by use of the 4 fixing bolts and nyloc nuts provided.
2. Ensure the deck / bulkhead being used is strong enough for the weight required. Please refer to your vessel instructions if required. You may need a separate bracing plate on the rear of the mounting foot.
3. Install the mount to the vessel first, then you can run the power cable for the antenna through the IP rated gland in the mount. Secure the power supply in the void neatly
4. Attach the FLAT PANEL HIGH PERFORMANCE ANTENNA to the top of the mount, ensuring the waterproof gasket is used to create a water seal.
5. Using the ratchet, angle the antenna to be 8° as requested by STARLINK. This can be done by making the base plate of the void HORIZONTAL
6. Ensure the ratchet bolt is tightened.

Cleaning Instructions

To clean the mount, use mild dishwashing liquid (one that is not harsh to the hands and without ammonia) in lukewarm water.

WARNING: Do not let paint solvents, cleaning solvents, or adhesive caulking come in contact with the mount. Chemicals in these materials might destroy the finish.

Supplied Parts

- 1 x 7187-SL Mount
- 4 x Fixing Bolts
- 1 x Neoprene Gasket

