



Dolphin[®] charger



NEW

12V 24V

60A → 100A

ISO 8846



DolPro evo3 Series

This new range of chargers is the result of the latest technologies in the world of power electronics. After several years of development we are thrilled to introduce PRO EVO3. These chargers represent a leap into the future with unparalleled performance and benefits. These products will fit perfectly in your battery charging system for your boat. These new chargers offer the best power to space ratio on the market with unmatched performance!

Ultra-compact and lightweight

Thanks to the new electronics this new generation of product is 30 to 60% lighter than the previous one. The weight of the 24 volt 100 amp unit is just under 4 kg.

4 Independent isolated outputs

All PRO EVO3 offer 4 independent isolated DC outputs. It allows to simplify the charging system consisting of several battery banks.

NMEA 2000

NMEA 2000 plug & play communication skills. All PRO EVO3 chargers feature CAN communication port including certified N2K port with latest PGEN.

High-Efficiency DSP technology

PRO EVO3 Chargers deliver full power even at very high temperatures (up to 50°C/122°F). This “no derating” feature is quite unique on the market.

Selectable battery chemistries

8 Selectable charging profiles including Lead Acid, Gel, AGM, Lithium-Ion batteries with temperature compensation.

Ignition Protected

PRO EVO3 12.90 is now ISO 8846 and SAE J1171 certified.



This project is co-financed by the European Regional Development Fund

Technical specifications

	12V 90A	24V 40A	24V 60A	24V 100A
Input				
Input voltage	115/230V (+/-15%)			230V (+/-15%)
Frequency	50/60 Hz			
Power factor Cos j	> 0,95			
Efficiency	92%			
Max. Consumption	1450 VA	1300 VA	1950 VA	3200 VA
Derating @ 115V	No	No	1300 VA	No
Fuse (Glass type 6,3x32mm)	T20A			
Output				
Number of output	4 isolated (Full power)			
Charging profiles	Open lead acid / Sealed lead acid / Lead calcium / Spiral cell AGM / Winterizing / Odyssey Marine / GEL/ Power supply / LiFePO4#1 + BMS / LiFePO4#2 + BMS			
Charge profile selection	Rotary switch 10 positions			
Charging algorithm	I.U.o.U			
Temperature compensation	+/-2,5 mV / °C (Ext temp sensor supplied)			
Max. Amp (+/-5%)	90A	40A	60A	100A
Battery capacity	350 ÷ 900 Ah	200 ÷ 400 Ah	250 ÷ 600 Ah	400 ÷ 1000 Ah
Fuse (auto mini)	5F25A	3F25A	3F25A	5F25A
Protections				
Auto restart when alarm disappears (output short circuit, output voltage, internal over temp)	Output current limited / Output short circuit / Overload output voltage / Reverse polarity / Over temperature			
General				
Display	LED Panel (State of charge, Power, Alarms)			
Operating temperature	-10°C to +55°C (Full power till +50°C)			
Storage temperature	-20°C to +70°C			
Humidity	10% to 95% (without condensation)			
Convection	Force fan adjustable speed cooling			
Mounting	Wall mounted 4 x M4 Screws			
On/Off Operation	Front Push button or dry contact NO (terminal block 2pin 1mm ²)			
Input Alarm	Dry contact NO (terminal block 2pin 1mm ²)			
Output alarm contact	x2 0,5A 30V NO (terminal block 2pin 1mm ²)			
Battery temperature sensor	External sensor (terminal block 2pin 1mm ²)			
CAN Bus connection	x2 Micro-Fit 3.0			
Communication standard	Navicolor by Scheiber, NMEA 2000			
Standards				
Safety	EN 60335-1 / EN60335-2-29			
Mechanical & Environmental	IEC 60068-2-30/1/52 (climatic, salt spray)			
EMC	EMC 2014/30/EU Directive			
Ignition Protection	SAE J1171/ISO 8846	No		
Part Number	399454	399474	399464	399484
Enclosure				
Material and colour	Polycarbonate white			
Dimensions H x W x D (mm)	284 x 360 x 122 mm (11.2 x 14.2 x 4.8 inch)			
Weight kg (lbs)	3,5 Kg (8 lbs)			3,9 Kg (9 lbs)
Enclosure class	IP22			
AC Connection	WAGO WINSTA Type 770-813 connector			
DC Terminal	4M8 Terminals			