

## Low Friction Rings with Dyneema Loop

The Barton Low Friction Rings (High Load Eyes) with loop is available in 4 sizes and can be used in various applications on board including Baber hauler, preventers, mast base block, tidies, emergency, occasional and toe rail blocks etc.

The High Load Eye combined with the Dyneema loop gives you a fast, efficient, simple and extremely strong solution to changing the direction of any line. The HV500 anodised aluminium eye is designed to have very good wear resistant properties with low friction, this combined with the Dyneema loop gives you exceptional low weight to very high performance load ratio.



Part Number

PART NO	EXTERNAL DIA Ø		INTERNAL ROPE DIA Ø		BORE DIA Ø		LOOP LENGTH		SWL		WEIGHT	
	MM	INCH	MM	INCH	MM	INCH	MM	INCH	KG	LBS	G	OZ
60460	26	1	6	1/4	12	7/16	100	3 15/16	750	1653	11	0.39
60463	38	1 1/2	10	3/8	16	5/8	180	7 1/16	1500	3300	45	1.6
60461	52	2 1/16	12	7/16	22	7/8	230	9 1/16	2400	5291	75	2.6
60462	65	2 9/16	16	5/8	28	1 1/8	310	12 3/16	3600	7964	140	4.9

