

C-Class CONNECT – Rain Manager

Rainwater harvesting

DehoustCONNECT makes the proven C-Class even safer and more user-friendly.

With an extension vessel, the switching frequency of the pump can be reduced and the service life extended. Information on design can be found in our data sheets.



Article no.	Description	Flow rate Q_{max}	Flow volume H_{max}
814354	CONNECT 6-40 C-Class	6 m ³ /h	46 m
814355	CONNECT 8-40 C-Class	9 m ³ /h	42 m
814356	CONNECT 8-50 C-Class	9 m ³ /h	58 m

Rain Manager accessories C-Class CONNECT

Article no.	Description
812448	Rainwater tank level indicator
812483	Rainwater stop 1 1/4"



Industry 4.0

Equipment and advantages C-Class

- ▶ DehoustCONNECT control for regulating and monitoring the system functions
- ▶ Drinking water feeding type AA via KTW W270 approved solenoid valve with automatic closing should there be a malfunction (power failure)
- ▶ Powerful double pump system with pressure sensor and adjustable switching points
- ▶ **Extension vessel 8 litres**
- ▶ Moisture detector for installation room
- ▶ Web-enabled CONNECT control for remote inquiry and operation via smartphone, tablet or PC



C Class



Hybrid system

CONNECT hybrid system including feeder pump

The hybrid system, consisting of double pump system CONNECT with storage tank AQF, is intended for use in large-scale rainwater systems. It switches the submersible pump included with the system (with float switch and additional dry-running protection) in the cistern and, if required, automatically controls the switchover to drinking water operation in accordance with EN 1717.

The electrically-controlled and monitored magnet valve avoids pressure surges in the network and closes automatically in the event of a power failure. DehoustCONNECT prevents stagnation in the supply line in line with the relevant standards.



Article no.	Description	Flow rate Q_{max}	Conveying height H_{max}
814324	CONNECT 6-40 Hybrid	6 m ³ /h	46 m
814325	CONNECT 8-40 Hybrid	9 m ³ /h	42 m
814326	CONNECT 8-50 Hybrid	9 m ³ /h	58 m
814329	CONNECT 14-40 Hybrid	14 m ³ /h	47 m
Accessories			
812448	Rainwater tank level indicator in the CONNECT control unit		
812483	Rainwater stop 1 1/4"		
814335	Additional feed-in unit 1" with receiver tank		

The feeder pump is designed for a max. conveying height of 5 m and pressure line of 25 m.