

Supply Pedestal T4

USER-FRIENDLY SUPPLY PEDESTAL DESIGNED FOR MODERN MARINA AND CAMPER LIFE

Betally T4 is a user-friendly supply pedestal for power and water in marinas and campsites. The elegantly designed supply pedestal is robust, and has several applications. Among other things, it offers dimmed light, so your guests can see what they are doing, while an energyefficient LED lamp provides a mood setting atmosphere on the piers and harbour. T4 complies with all EU-standards and is maintenance free, which ensures problem-free daily use. The pedestal is available in a number of high-quality models, and besides power and water supply for your guests, it also offers the possibility for remote control and reading of power through our administrative systems. It can also be used as lighting source at night. Safety and user-friendliness are in focus. The individual relays, meters and joint code keyboard with touch-free card reader are placed safely behind a storm-proof and self-closing front lid. The panel is straightforward and easy to operate, and the power pedestal can always be equipped, combined, and extended according to your needs and wishes.



Quality that survives many years of outdoor use.

All Betally supply pedestals are developed and manufactured in our factory in Denmark, where skilled employees use robust and durable materials. Our products comply with all EU-standards and legal requirements for this type of installation. The pedestal is made of anodised aluminium, while bolts, shafts and screws are made of acid-proof steel, which means minimal maintenance. You will always be able to welcome your guests to an efficient marina or harbour in beautiful surroundings.



Supply Pedestal T4



Height:
106 cm or 126 cm

Weight:
7 - 20 kg.

Power outlets:
1 to 6 sockets 16A to 63A single or three-phase.

Water taps:
Option for 2 x 1/2" (or 3/4") water taps plus hose holder.

Safety:
Every outlet is protected by a MCB and RCD or a RCBO.

Lighting at the top:
7 watts LED.

Temperature:
-20 to +60-degree Celsius.

Density:
IP44 (IP56 as option).

Standard:
IEC 61439-7.

Mounting:
Delivered with standard flange.

Power connection:
CU, 2.5 to 50 mm² via main switch

Water connection:
20 - 25 mm PL-pipes.

Materials:
Pedestal: Weather-resistant, anodised aluminium 6063.
Screws and bolts: Acid-proof steel A4.

Maintenance:
None.

Subject to change without notice.

