

N1 Walk behind floor scrubber

N1



lithium battery

Technical parameter	
Solution Capacity	6L
Recevery Tank Capacity	9L
Diameter of Brush Disc	280mm
Suction Width	340mm
Theoretical Cleaning Efficiency	800m ² /h
Machine Dimensions	584*401*1044mm

Application scenario:

Suitable for cleaning various hard surfaces , restaurants , shopping malls , hospitals , office buildings , train stations , airports , factories , etc

N2 Walk behind floor scrubber

N2



lead-acid battery

Technical parameter	
Solution Capacity	35L
Recevery Tank Capacity	40L
Working Width	500mm
Squeegee Width	800mm
Theoretical Cleaning Efficiency	2250m ² /h
Machine Dimensions	1300*800*1060mm

Application scenario:

Suitable for cleaning various hard surfaces , restaurants , shopping malls , hospitals , office buildings , train stations , airports , factories , etc

N3 Hand push single brush floor scrubber

N3



Large capacity sewage tank

Sewage tank with float design, full of water automatic shutdown

Automatic delay design

Automatic delay of 10 seconds to clean up the stains under the current operation.

Arc type suction skimmer

The water can be completely withdrawn in a 180°turn.

Convenient operation panel

Operator interface is simple and subjective, one button start is operator friendly.

Separate waste collection basket

Automatic waste filtration for improved operator efficiency.

Technical parameter	
Solution Capacity	45L
Recevery Tank Capacity	50L
Working Width	500mm
Squeegee Width	800mm
Theoretical Cleaning Efficiency	2250m ² /h
Machine Dimensions	1300*800*1060mm

Application scenario:

Cleaning of various hard floors (shopping malls, hospitals, office buildings, train stations, airports, factories, etc.)

lead-acid battery

N3-plus Walk behind driven floor scrubber

N3-Plus



Large capacity sewage tank

Sewage tank with float design, full of water automatic shutdown

Automatic delay design

Automatic delay of 10 seconds to clean up the stains under the current operation.

Arc type suction skimmer

The water can be completely withdrawn in a 180°turn.

Convenient operation panel

Operator interface is simple and subjective, one button start is operator friendly.

Separate waste collection basket

Automatic waste filtration for improved operator efficiency.

With drive motor, easy to work with lower power.

Technical parameter	
Solution Capacity	45L
Recevery Tank Capacity	50L
Working Width	500mm
Squeegee Width	800mm
Theoretical Cleaning Efficiency	2250m ² /h
Machine Dimensions	1300*800*1060mm

Application scenario:

Cleaning of various hard floors (shopping malls, hospitals, office buildings, train stations, airports, factories, etc.)

lead-acid battery

N5 Small ride-on scrubber

N5

Induction floating ball in the sewage tank,It can protect the motor well.

Because it is wide opening with no hard comer of the tank.So it is easily to clean.

Equipped self-check function,it ls easy and efficient to maintain.

More thick water tank,made of PE materials,light,Preservative durable,good sealing.

Well-known brush motor, stable performance and more durable.

With ECO,save energy,environmentfriendly.

With rubbish gather basket,It can filter garbage,Prevent blocking and reduce the fault probability of machine caused by blockingor rubbishes.

Touch control panel,easy to handle.

Technical parameter	
Solution Capacity	75L
Recevery Tank Capacity	80L
Working Width	560mm
Squeegee Width	900mm
Theoretical Cleaning Efficiency	3500m ² /h
Machine Dimensions	1340*900*1200mm

Application scenario:

Cleaning of all types of hard floors (shopping centres, hospitals, office buildings, railway stations, airports, factories, etc.)

lead-acid battery



N5 PLUS Small ride-on scrubber



Induction floating ball in the sewage tank,It can protect the motor well.

Because it is wide opening with no hard comer of the tank.So it is easily to clean.

Equipped self-check function,it Is easy and efficient to maintain.

More thick water tank,made of PE materials,light,Preservative durable,good sealing.

Well-known brush motor, stable performance and more durable.

With ECO,save energy,environmentfriendly.

With rubbish gather basket,It can filter garbage,Prevent blocking and reduce the fault probability of machine caused by blockingor rubbishes.

Touch control panel,easy to handle.

lead-acid battery

N5 PLUS

Technical parameter	
Solution Capacity	75L
Recevery Tank Capacity	80L
Working Width	700mm
Squeegee Width	900mm
Theoretical Cleaning Efficiency	4000m ² /h
Machine Dimensions	1340*900*1200mm

Application scenario:

Cleaning of all types of hard floors (shopping centres, hospitals, office buildings, railway stations, airports, factories, etc.)

N6 Small ride-on scrubber

N6



Large capacity sewage tank

Sewage tank with float design, full of water automatic shutdown

Automatic delay design

Automatic delay of 10 seconds to clean up the stains under the current operation.

Arc type suction skimmer

The water can be completely withdrawn in a 180°turn.

Convenient operation panel

Operator interface is simple and subjective, one button start is operator friendly.

Electronic Parking Brake System

Automotive Grade Brake Release Brake

Technical parameter	
Solution Capacity	80L
Recevery Tank Capacity	90L
Working Width	700mm
Squeegee Width	1000mm
Theoretical Cleaning Efficiency	4000m ² /h
Machine Dimensions	1300*1000*1220mm

Application scenario:

Cleaning of all types of hard floors (shopping centres, hospitals, office buildings, railway stations, airports, factories, etc.)

lead-acid battery

N7 Ride-on scrubber

N7



Large capacity sewage tank

Sewage tank with float design, full of water automatic shutdown

Automatic delay design

Automatic delay of 10 seconds to clean up the stains under the current operation.

Arc type suction skimmer

The water can be completely withdrawn in a 180°turn.

Convenient operation panel

Operator interface is simple and subjective, one button start is operator friendly.

Electronic Parking Brake System

Automotive Grade Brake Release Brake

Technical parameter	
Solution Capacity	130L
Recevery Tank Capacity	140L
Working Width	850mm
Squeegee Width	1080mm
Theoretical Cleaning Efficiency	5200m ² /h
Machine Dimensions	1520*1080*1350mm

Application scenario:

Cleaning of all types of hard floors (shopping centres, hospitals, office buildings, railway stations, airports, factories, etc.)

lead-acid battery

S3 Ride-on sweeper

S3



- (1) driving sweeper spray dust suppression sweeping;
- (2) sprinkler spray does not raise dust, standard with water spray device, effectively reduce dust, avoid secondary pollution no longer need to worry about the dust of the sky;
- (3) stable driving easy to climb the slope without overturning, driving easily over the road speed bumps, small slopes, small obstacles;
- (4) hydraulic double disc brake braking device, to ensure the safety of the machine work, to prevent the occurrence of runaway, side slip and loss of steering ability;
- (5) Drawer type large dust box, more convenient dumping of garbage.

Technical parameter	
Sweeping Width	1250mm
Main Brush Width	500mm
Clear Water Tank	22L
Trash Bin Tank	92L
Theoretical Cleaning Efficiency	7200m ² /h
Machine Dimensions	1108*1200*1320mm

lead-acid battery

Application scenario:

Suitable for small car parks, entrances and outdoor areas in hotels and supermarkets, as well as for internal floors in warehouses and factories.

SD430 Multifunctional Single Discs

SD430



Power line

Powerful 1.5 HP

Provide enough power for cleaner cleaning

Large capacity 3-core waterproof wire

More waterproof, wear-resistant and corrosion-resistant, more flexible for installation and use.

Large-capacity starting capacitor

Improve the efficiency of equipment starting, improve the life of the equipment

Insulated operating handle

Higher safety, more practicality, longer service life

Chassis non-marking anti-collision rubber edge

Lightweight design, vibration and noise reduction, convenient maintenance

Triple planetary metal gearbox

Large reduction ratio, high output torque, wide range of reduction, high accuracy of gearbox backlash.

Technical parameter	
Power	1.5HP
Machine Speed	150Rpm
Chassis Dimeter	17inches
Voltage	220V
Product Weight	48Kgs
Power line	13m

Application scenario:

Office buildings, hotels and other types of floor cleaning: such as ceramic tile, terrazzo, wool, emery, carpet and so on.

SD430-HD Floor Polisher

SD430-HD



Technical parameter	
Power	2.5HP
Machine Speed	175Rpm
Chassis Diameter	17inches
Voltage	220V
Product Weight	52Kgs
Power line	13m

- 1) 2.5hp provides sufficient power;
- 2) Triple planetary metal gearbox;
- 3) Large capacity starting capacitor;
- 4) Metal powder coating plus epoxy numerical surface treatment for the body,
- 5) Large capacity 3-core waterproof electric wire;
- 6) insulated operating handle;
- 7) Chassis non-marking anti-collision rubber edge.

Power line

Application scenario:

Renovation and maintenance of all types of marble floors.

CT800 Three Speed Air Blow Dryer

CT800



Powerful, high-efficiency motors

Powerful and efficient motor, prolonging the service life

High strength metal alloy wind blade

High-strength metal alloy wind blade, durable

Thickened engineering plastic shell

Thickened engineering plastic shell, tightly protect the body

Extended handle

Extended handle, easy to use

Integral injection moulding of the shell

Overall injection moulding shell, beautiful and durable; wrapped large wheels to move more conveniently.

10m power cord

10m power cord, easy to connect the power, blow drying radius is bigger.

Technical parameter	
Power	800W
Voltage	200V/50HZ
Max Speed	1390Rpm
Air Volume	30m ² /min
Wind Speed	Three adjustable gears
Power line	10m
Package Size	527*450*545mm

Application scenario:

Blowing air on all types of floors and enhancing air movement in humid environments.

Power line

ST02 3 in 1 carpet vacuum cleaner

ST02



Power line

Technical parameter	
Working Width	380mm
Safety Factor	
Voltage	220V/50Hz
Suction motor	1200W
Clear Water Tank	38L
Sewage Tank	30L
Cable length	15m
Brush Rotation Speed	900Rpm
Weight	44Kgs
Machine Dimensions	900*460*860mm

Application scenarios:

Hypermarkets/ Malls/ Supermarkets/ Airports/
High-speed rail stations/ Clubs/ Hotels/ Guest
Houses/ Office/Theater etc.

ST12 Silent Vacuum Cleaner

ST12



Power line

Technical parameter	
Power	800W
Voltage	220V/50HZ
Vacuum Degree	24Kpa
Hose Length	2m
Volume	12L
Power line	10m

Application scenarios:

Hotel rooms, offices, meeting rooms and other types of floors in a small area of vacuuming (hard floors, carpets, etc.)

ST20 Economical Vacuum Cleaner

ST20



Power line

Technical parameter	
Power	1200W
Voltage	220V/50HZ
Vacuum Degree	18Kpa
Hose Length	1.5m
Volume	20L
Power line	5m

- 1) Silent motor with double insulation;
- 2) Vacuum system for bypass return refrigeration;
- 3) Accessory storage system;
- 4) Stainless steel drum body;
- 5) Filter mesh vibrating dust screen;
- 6) Washable filters.

Application scenarios:

Minor vacuuming of various types of floors in offices, conference rooms, etc. (hard floors, carpets, etc.)

ST800 large capacity vacuum suction machine

ST800



Stainless steel barrels

Better performance stainless steel, with corrosion and crack resistance

Liquid float valve

Complete sealing over a wide range of pressures and temperatures

Tiltable bucket

Helps one to easily handle various pouring operations

Anti-static shock absorber

Cushions body shocks and dampens body vibrations. Suppresses vehicle hopping and improves tyre-to-ground grounding for vehicle safety

Vacuum system with bypass circulation cooling

Saves energy costs by reducing energy consumption

Technical parameter	
Power	3600W
Voltage	220V/50HZ
Vacuum Degree	21Kpa
Air Flow	132L/S
Volume	80L
Power line	10m

Application scenario:

Hotels, properties, hospitals and other ground cleaning after the suction or leakage of emergency treatment of accidents, but also vacuum cleaner

ST800 random accessories:

Hose set, water suction pickup head, flat nozzle suction, filter bag, extension pole, brush, dust pickup head.

Power line

HC-2 High Pressure Cleaner(Cold Water)

HC-2

Motor overheating protection device

Due to overloading, phase sequence disorder, voltage instability and other causes of motor temperature rises above the safe range, the thermal protector will automatically cut off the power supply to prevent motor overheating damage.

Stainless steel suction and discharge valve components

Large exhaust volume, fast exhaust speed

Low noise design

Low noise reduces noise hazard, quieter

Stepless section regulator

Reduces pressure fluctuations in the hydraulic system and saves energy.

Ergonomic mobile handle

Ensures stability and comfort when holding the unit.



Technical Parameter	
Power	2200W
Voltage	230V/50Hz
Pressure	30-150 Bar
Rate of flow	9L/min
Water temperature	40°C
Motor speed	1450RPM
Machine dimensions	680*490*490mm

Application scenario:

Blowing air on all types of floors and enhancing air movement in humid environments.

HC-6 High Pressure Cleaner(Hot Water)

HC-6



Independent motor motor

Significantly lower power consumption and less environmental pollution

Upright boiler

Small footprint, higher thermal efficiency, more convenient maintenance Maintenance difficulty Relatively small, more convenient.

Stainless steel high-pressure and low-pressure valves

Strong corrosion resistance, can be adapted to use in a variety of extreme environments, not easy to rust, deformation and wear.

Outlet water temperature up to 140°C

Adopting high temperature and high pressure water flow for cleaning, it can quickly and effectively remove the dirt and grease on various surfaces, and at the same time, it has the effect of sterilisation and disinfection.

Technical Parameter	
Power	7300W
Voltage	400V/50Hz
Pressure	30-200 Bar
Rate of flow	450-900L/h
Maximum Inlet water temperature	40°C
Motor speed	1450RPM
Machine dimensions	1070*680*830mm
Diesel tank	18L

Application scenario:

Heavy grease rinsing of floors and high temperature steam abatement of livestock farming environments.