

YOUR ONBOARD SAFE CHOICE

WORLD LEADER IN MARINE FIRE SUPPRESSION TECHNOLOGY

Carbon Monoxide Alarm

Surface Mount, White, Battery Operated, EU

SB-054-REV-A

This CO alarm displays the real-time CO concentration (ppm) on an easy-to-read LCD.

It will also inform you of any faults, low batteries, and an end-of-life indication.

Equipped with a cutting edge Figaro electrochemical CO sensor that delivers accurate CO detection and responds quickly.

Includes an automatic self-test function to ensure the alarm is always functioning properly.



| Product specifications | |
|-------------------------------|--|
| Item Model Number | XC01-R |
| Silence Duration | ≤ 9 minutes |
| Operating Life | 10 years |
| Display | LCD |
| Power Source | CR123A or CR2/3A (replaceable battery) |
| Indicator Light | LED (red/yellow/green) |
| Sensor Type | Electrochemical |
| Color | White |
| Safety Standards | EN 50291 2018 |
| Material | ABS |
| Standby Current | < 7 μA (avg) |
| Installation Method | Screw Fitings supplied |
| Alarm Current | < 70 mA (avg) |
| Usage | Indoor use only |
| Operating Temperature | 10-100°F (4.4-37.8°C) |
| Product Weight | 0.19 lb (88 g) |
| Operating Relative Humidity | 10% - 85% (non-condensing) |
| Product Dimensions | 5.3 x 2.5 x 0.9 in (135 x 63 x 24 mm) |
| Alarm Loudness | \geq 85 dB at 19 ft (3 m) |
| Package Contents | 1 Alarm Unit, 2 Screws, 2 Anchor Plugs, 1 User Manual User Manual |



Note

Information contained on this document is offered with no warranties or representations as to accuracy or completeness. Additionally, Sea-Fire Marine reserves the right, in its sole discretion, to modify product, alter product specifications, and/or amend this document without notice.

Approvals

All models on this data sheet include all of the following approvals: **CE and RoHS**