

Electronic Ballast for Amalgam Lamp



Model No.	Current & Input Voltage	Input Power (watt)	Size (mm)	Lamp Current (A)	Lamp Power (watt)	Cert.	Function	Lamp Models
PH9-2100-320	1.64A@230V	378	250*95*45	2.0-2.2	1*320 2*172	CE	LED 5V N	1*GPHHA1000T6, GPHHA1554T6, NNI300/147XL, TUV325WXPT 2*GPHHA650T6, GPHHA843T6
PH9-2100-320A	3.15A@120V	378	250*95*45	2.0-2.2	1*320 2*172		LED 5V N	1*GPHHA1000T6, GPHHA1554T6, NNI300/147XL, TUV325WXPT 2*GPHHA650T6, GPHHA843T6
EP9-2100-320	1.49A@230V	341	250*108*57	2.0-2.2	80-320	CE	LED 5V	GPHHA1000T6, GPHHA1554T6, NNI300/147XL, TUV325W XPT
PH9-AL-400	1.89A@230V	434	250*95*45	1.8~4.6	150~400	CE	LED 5V N	GPHHA1000T6 GPHHA1554T6 NNI300/147XL NNI400/147XL TUV325WXPT
PH10-5500-500	2.32@230V	525	250*141*65	5.5	200~500	CE	LED 5V N	GPHHVA843T10 GPHHVA1000T10 GPHHVA1148T10 GPHHVA1554T10
PH10-AL-500	2.32@230V	525	250*141*65	4.7~6.0	200~500	UL CE	LED 5V N	调档 GPHHVA843T10 GPHHVA1000T10 GPHHVA1148T10 GPHHVA1554T10
PH10-AL-800	3.7@230V	850	250*141*65	4.50~8.0	450~800	UL CE	LED 5V N	GPHHVA1520T10 GPHHA1554T10L/4P GPHHVA1600T10 GPHHVA357T12 GPHHVA843T12 GPHHVA1554T12 GPHHVA1600T12 GPHHVA1790T12
EPS10-AL-800	3.7@230V	850	310*150*75	3.0~8.0	400~800	CE	N D C	GPHHA1554T10L/4P GPHHVA1600T10 GPHHVA1554T12 GPHHVA1600T12 GPHHVA1790T12

LED — red/green, green indicator 5V — 0/5VDC signal

N — dry contact, external PLC output switching value, remote monitoring lamp normal/faulty

D — Adjust the output current and lamp power from 0-10V to realize the dimming function

C — Connect to PLC through 24VDC power supply to remotely control the lamp on/off intelligently