


Colorstar

→ LOGO MAT • INDOOR




→ WHY CHOOSE THIS MAT?

ColorStar mats feature your custom logo or artwork digitally printed on recycled PET material. Choose from 66 standard color options.

- The top layer of the mat contains **100% recycled PET material**
- Photographic Print Quality
- Incredible **stain resistance**: no cross staining, easy to clean
- Produced within **24 hours**
- Also available as unicolor mat

→ SPECIFICATIONS

Yarn	100% post-consumer recycled PET fibers, twisted and heat-treated <ul style="list-style-type: none">• Yarn weight: 900 g/m²
Backing	<ul style="list-style-type: none">• Primary backing: 100% recycled PET non-woven• Rubber backing: 100% nitrile rubber with 34% post-industrial recycled content in the polymer – For maximum oil resistance, durability, and performance. – Compression-molded with reinforced borders on all four sides• Thickness: 1.5 mm – Also available in 3mm rubber backing
Border	<ul style="list-style-type: none">• Thickness: 2.5 mm• Width: 2 cm
Other properties	<ul style="list-style-type: none">• Pile thickness: 11 mm• Total weight: 2,9 kg/m²
Safety	<ul style="list-style-type: none">• Static control: ISO 6356 (2012) Determination of the static electrical propensity – walking test: -0.3 kVolts. Satisfies IBM test requirements• Flammability: Cfl / s1 according EN 13501-1. Passes BS 4790 (1987) determination of the flammability of textile floor coverings: Low radius of effects of ignition.
Recommended use	Recommended for indoor commercial use at entryways, in lobbies, at front desks or anywhere you want to display your company logo, slogan, artwork, or message to customers/visitors or employees



→ STANDARD SIZES

60x85	75x85	85x115	85x150
85x300	115x180	115x200	115x240
115x250	115x300	150x200	150x240
150x250	150x300	200x200	200x300

→ SPECIAL SIZES

Max. size: 200 cm x 550 cm

Size Tolerance: +/- 2%


Weight Tolerance: +/- 5%

→ COLOURS



→ How much plastic bottles do we save?

60 x 85 → 33	115 x 200 → 147	150 x 250 → 240
75 x 85 → 41	115 x 240 → 176	150 x 300 → 288
85 x 115 → 62	115 x 250 → 192	200 x 200 → 256
85 x 150 → 82	115 x 300 → 221	200 x 300 → 384
85 x 300 → 164	150 x 200 → 192	
115 x 180 → 132	150 x 240 → 230	



→ CLEANING INSTRUCTIONS



Colorstar mats can be cleaned in several different ways:

1. They can be commercially laundered (see Laundering Instructions)
2. Vacuumed regularly (daily in high-traffic areas; weekly in lower-traffic applications)
3. Cleaned with an extractor, or hosed off as necessary to remove heavy soil

Hang to dry. Mats should always be dry before they are placed back in service.

Laundering Instructions

1. Flush, 2-3 Min. on a medium water level with a maximum temperature of 49°C
2. Flush (optional), 2-3 Min. on a medium water level with a maximum temperature of 49°C
3. Break, 2-3 Min. on a high water level with a maximum temperature of 49 °C
4. Rinse, 2 Min. on a high water level with cold temperature
5. Rinse, 2 Min. on a high water level with cold temperature
6. Extract on low speed, 1-2 Min.
7. Shake out with the drum turning, 1 Min.
8. Extract, on a maximum of 250G, 3-5 Min.
9. Dry (optional), 5-10 Min. with a maximum basket temperature of 82 °C
10. Cool down, 5 Min.

Additional recommendations

- For Heavy Soiled Mats, increase the temperature up to max. 60°C.
- The wash or rinse baths should have a pH between 6 and 9.5; use low pH non-ionic detergents.
- Do not overdry mats; Basket-temperature of the dryer should not exceed 82 °C.
- If mats are not dried, the final rinse can be increased to 49 °C. This will reduce moisture retention following extraction.
- Lay mats flat following removal from washer; allow mats to cool before rolling.

