



Intelligent Traffic Strobe Illuminator Solutions



Make it pass through the windscreen
at Night





Feature:

- Compact with integrated LED Light source.
- Auto detects the trigger width with flash duration.
- Stack effect Design for more efficiency by reducing heat.
- Extra long life with very low maintenance.
- IP66 housing for outdoor installation.

Applications:

- Face recognition behind windshield
- Traffic speed management
- Speed enforcement
- Vehicle type identification
- Automatic number plate recognition
- Rail container scanning
- Red light violation
- Toll management systems
- Weigh in motion
- HOV (High Occupancy Vehicle)

S series:

Intelligent Strobe Illuminator

Available WaveLength:

| | | | | | | | | | |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 460nm | 3000K | 4000K | 5600K | 730nm | 760nm | 780nm | 810nm | 850nm | 940nm |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|



Feature:

- Composite design for various applications.
- Support holder for Embedded, Antenna, Camera & Lens.
- Negative Pressure design to avoid the oil and dust pollution.
- Rotation Angle design to avoid the horizontal problem.

Applications:

- Traffic speed management
- Speed enforcement
- Vehicle type identification
- Automatic number plate recognition
- Traffic integrated device
- Rail container scanning
- Red light violation
- Toll management systems
- Weigh in motion

C series:

Compositd Traffic Device

Available WaveLength:

| | | | | | | | | | |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 460nm | 3000K | 4000K | 5600K | 730nm | 760nm | 780nm | 810nm | 850nm | 940nm |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|



Feature:

- Support any machine vision camera into ITS application.
- GigE vision composite cable with waterproof connector.
- Wide Range Power Input from 10~30VDC.
- Anti-Vibration : 5Hz~500Hz / 1 Grms/3 Axis.
- Anti-Shock : 15G, 11ms duration.

Applications:

- Mobility and boat
- Traffic speed management
- Speed enforcement
- Automatic number plate recognition
- Toll management systems
- Weigh in motion
- Traffic integrated device

M series:

Mobility Traffic Device

Available WaveLength:

| | | | | | | |
|-------|-------|-------|-------|-------|-------|-------|
| 3000K | 4000K | 760nm | 780nm | 810nm | 850nm | 940nm |
|-------|-------|-------|-------|-------|-------|-------|



Feature:

- Support any machine vision camera into ITS application.
- GigE vision composite waterproof connector & cable.
- Wide Range Power Input from 10~30VDC.
- Compact bollard design for parking lot.
- Available for embedded usage.

Applications:

- Car parking
- Traffic speed management
- Weigh in motion
- Automatic number plate recognition
- Traffic integrated device

P series:

Bollard Strobe Illuminator

Available WaveLength:

| | | | | |
|-------|-------|-------|-------|-------|
| 3000K | 760nm | 810nm | 850nm | 940nm |
|-------|-------|-------|-------|-------|



Feature:

- Super long range up to 300m.
- IP66 enclosure for outdoor installation.
- Compact LED Light source.
- Ultra high power -Low running cost.
- Automatic Day/Night switch.

Applications:

- Where light conditions are less than optimal

K series:

Continued Illuminator

Available WaveLength:

| | | | | | | | | |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 3000K | 4000K | 5600K | 730nm | 760nm | 780nm | 810nm | 850nm | 940nm |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|

