

Negli ammortizzatori MK Ibridi brevettati, la molla viene coadiuvata dagli elastomeri, a forma cilindrica, che da soli hanno un carico inerziale molto alto, unitamente alla molla, a partire dal singolo centrale fino ai 4 per ciascuna estremità, aumentano la capacità a fronte di importanti sollecitazioni, con un movimento progressivo che si adatta all'imbarcazione.

In the MK Hybrid patented shock absorbers, the spring is assisted by elastomers, in a cylindrical shape, which alone have a very high and non-progressive inertial load. However, together with the spring, from the single central one to the 4 at each end, increase capability in the face of major stresses, with a progressive movement that adapts to the boat.

ARTICOLO

CODE

**MK 55
IBRIDO/HYBRID**

TONNELLATE BARCA

Da 30 a 90 t

BOAT WEIGHT

From 30 up 90 t

**FORZA AMMORTIZZANTE
PROGRESSIVA**

Da 450 a 2.500 Kg

*PROGRESSIVE
DAMPING FORCE*

From 992,08 up 5.511,56 lb

CORSA AMMORTIZZATORE

125 mm

SHOCK ABSORBER RIDE

4,92"

CARICO DI ROTTURA

30.000 Kg

BREAKING LOAD

66.138,68 lb

DIMENSIONI/PESO

5,40 Kg - 11,91 lb

DIMENSIONS/WEIGHT

108 x 474 mm 4,25 x 18,66"



MK 55 HYBRID