

# DOMUS



**5603**  
Trasparente  
Transparent  
Transparent



**5606**  
Bianco 9010  
Weiß 9010  
White 9010



**5607**  
Bianco 9016  
Weiß 9016  
White 9016



**5617**  
Jasmin 1013  
Jasmin 1013  
Jasmin 1013



**5618**  
Manhattan 7035  
Manhattan 7035  
Manhattan 7035



**5608**  
Grigio chiaro 7047  
Hellgrau 7047  
Bright grey 7047



**5616**  
Grigio perla 7040  
Perlgrau 7040  
Pearl grey 7040



**5600**  
Grigio cemento 7032  
Zementgrau 7032  
Cement grey 7032



**5614**  
Grigio 7030  
Grau 7030  
Grey 7030



**5615**  
Metallic grigio 7024  
Grau Metallic 7024  
Metallic grey 7024



**5605**  
Aorio 1013  
Elfenbein 1013  
Ivory 1013



**5623**  
Vaniglia 1015  
Vanille 1015  
Vanilla 1015


## Neutral curing silicone sealant with anti-mould agent and low modulus of elasticity.

Domus is a neutral silicone sealant with a low modulus of elasticity, resistant to UV rays and atmospheric agents, ideal for use on façades, roofs, in interior fittings in the marine industry, tinsmithing, and in door and window frames. The presence in the formulation of an agent with antimicrobial and anti-algal action makes it suitable for use in sanitary environments: the product resists boiling water and washing with chemically aggressive detergents, thus contributing to the hygiene of surfaces. Thanks to its neutral cross-linking, it does not develop unpleasant odours during application, does not release acid or basic substances that can corrode metal substrates and does not affect paints. It has excellent adhesion on both porous (masonry, concrete, plaster, wood) and non-porous (metal, plastic, glass, enamelled and porcelain surfaces) substrates. Domus is classified as a non-structural sealant for facades (type F-EXT/INT-CC 25 LM) in accordance with EN 15651-1, for glazing (type G-CC 25 LM) in accordance with EN 15651-2 and for sanitary applications (type S1) in accordance with 15651-3.

### Domus is ideal for:

- Elastic sealing of expansion joints with 25% elongation on the building envelope and roofs
- Matching joint sealing on wooden profiles in the furniture and marine industries
- Waterproof and mould-resistant sealing of joints in bathrooms, kitchen and spas
- Joint sealings in contact with glass
- Sealing of joints between window frame and wall

torggler.com



**5610**  
Bahama 1001  
Bahama 1001  
Bahama 1001



**5611**  
Beige  
Beige  
Beige



**5620**  
Nocciola 1011  
Haselnussbraun 1011  
Hazelnut 1011



**5619**  
Marrone 1019  
Braun 1019  
Brown 1019



**5613**  
Cioccolata 8003  
Schokoladenbraun 8003  
Chocolate 8003



**5622**  
Terracotta 3012  
Terracotta 3012  
Terracotta 3012



**5621**  
Noce 8011  
Nussbraun 8011  
Walnut 8011



**5612**  
Castano 8028  
Kastanienbraun 8028  
Chestnut 8028



**5624**  
Verde 6005  
Grün 6005  
Green 6005



**5598**  
Antracite 7022  
Anthrazit 7022  
Anthracite 7022



**5604**  
Antracite 7016  
Anthrazit 7016  
Anthracite 7016



**5609**  
Nero 9005  
Schwarz 9005  
Black 9005



**Torggler**