

Electronic Ballast

EPS8 Series



Model No.	Current & Input Voltage	Input Power (watt)	Size (mm)	Lamp Current (A)	Lamp Power (watt)	Cert.	Function	Lamp Models
EPS8-180-2/10	0.10A@230V	22	136*60*32	0.16-0.18	4-10	CE	*LED	2*GPH135T5/4W, GPH212T5/6W, GPH287T5/8W, GPL5W, GPL7W, GPL9W, GPL11W, TUV4W, TUV6W, TUV8W, LTC4T5, LTC6T5, LTC8T5
EPS8-180-2/10A	0.19A@120V	22	136*60*32	0.16-0.18	4-10		*LED	2*GPH135T5/4W, GPH212T5/6W, GPH287T5/8W, GPL5W, GPL7W, GPL9W, GPL11W, TUV4W, TUV6W, TUV8W, LTC4T5, LTC6T5, LTC8T5
EPS8-180-2/10U	0.10A@230V 0.19A@120V	22	136*60*32	0.16-0.18	4-10	CE	*LED	2*GPH135T5/4W, GPH212T5/6W, GPH287T5/8W, GPL5W, GPL7W, GPL9W, GPL11W, TUV4W, TUV6W, TUV8W, LTC4T5, LTC6T5, LTC8T5
EPS8-425-2/36	0.36A@230V	82	136*60*32	0.38-0.43	21-41	CE	*LED	2*GPH436T5, GPH843T5, TUV25WT5, TUV36T5, GPL36W
EPS8-425-2/36A	0.69A@120V	82	136*60*32	0.38-0.43	21-41		*LED	2*GPH436T5, GPH843T5, TUV25WT5, TUV36T5, GPL36W
EPS8-425-40	0.20A@230V	45	136*60*32	0.38-0.43	21-41	CE	*LED	GPH436T5, GPH843T5, TUV25WT5, TUV36T5, GPL36W
EPS8-425-40A	0.38A@120V	45	136*60*32	0.38-0.43	21-41		*LED	GPH436T5, GPH843T5, TUV25WT5, TUV36T5, GPL36W
EPS8-425-40N	0.20A@230V	45	136*60*32	0.38-0.43	21-41	CE	N	GPH436T5, GPH843T5, TUV25WT5, TUV36T5, GPL36W
EPS8-540-55N	0.26A@230V	60	136*60*32	0.46~0.54	55	CE	N	GPL55W, T8 25W
EPS8-800-2/60	0.56A@230V	130	136*60*32	0.8	28~60	CE	*LED	2*GPL35W GPL60W GPH357T5HO GPH436T5HO
EPS8-800-2/60A	1.08A@120V	130	136*60*32	0.8	28~60		*LED	2*GPL35W GPL60W GPH357T5HO GPH436T5HO

*Tailed LED is optional *B-Buzzer is optional

LED — red/green, green indicator

N — dry contact, external PLC output switching value, remote monitoring lamp normal/faulty